
## **DLS306 LED LIGHT**







**DLS306** 







274-DLS306-U sold separately

## **FEATURES & BENEFITS**

- Maximum light output in a minimum package
- Six Star Generation IV LEDs
- 12 customer selectable flash patterns, in two phases, plus steady-on
- New redesign allows steady burn activation through an independent wire
- Programmable modes include:
- Dual-color flashing mode and steady side overrides flashing (default)
- Dual-color flashing and opposite side continues flashing when steady side activated
- One color for flashing mode and other color for steady mode
- Amber now 2X brighter than before
- · Only options with white will have steady burn override
- S-Link System<sup>™</sup> synchronizing capabilities other Star LED units
- Circuitry is fully encapsulated within the housing for vibration and water resistance Specially engineered lens with diffusing optics for wider coverage

- Versatile design allows this light to be mounted in just about any location and in any direction
- · Completely self-contained no separate flasher needed
- Interior/exterior mount
- Kit includes a snap-on polycarbonate bezel that hides screw heads and provides for a clean install screw heads for a clean install
- Black bezel standard. Optional Chrome or White bezels available
- Dimensions: 1<sup>7</sup>/<sub>8</sub>"H X 2<sup>9</sup>/<sub>16</sub>"W x <sup>7</sup>/<sub>8</sub>"D
- Voltage: 10-30V DC
- Amp draw: 1.2 amps (max)

•	Color	combinations:	



PAKI	DESCRIPTION
DLS306	Mini-Comet™, Black bezel
DLS306C	Mini-Comet™, Chrome bezel

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF143 Rev-D 05-11-2023



FOR MORE INFORMATION VISIT OUR WEBSITE. STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC

455 Rochester St., Avon, NY 14414 Phone: 585-226-9500 | Fax: 888-478-2797

