SS650, SS651





FEATURES & BENEFITS

- · Combine small size with big power
- Ideal for volunteers and vehicles with limited mounting space
- Wail, Yelp, Air Horn, Phaser, and Manual
- Positive and negative switching for Auxiliary inputs
- 20 programmable siren tones (Simulated mechanical wail and manual, eight air horn tones)
- Drives one 100 watt speaker
- New connector requires no special terminals allowing you to retrofit any old siren harness install with a wire stripper and screw driver
- Auxiliary enable can be used to enable a siren/air horn tone; or for duplexed hands free tone cycling
- Dip switches and push button for option selection
- High and low voltage shutdown protection
- Diagnostic LED

- Self-resetting circuit protection against speaker shorts
- Replaceable fuse
- Ships complete with positive locking connector, mounting bracket (LCS650 only - U bracket), hardware, and instructions
- Dimensions: SS650 2"H x 6"W x 5"D, SS651 - 2"H x 6⁵/16"W x 4"D, SS651-CH - 2 ¼"H x 3"W x 1⁹/16"D
- Output: 100 watts (1 speaker)
- Voltage: 10 16V DC
- Frequency: 675-3000Hz
- Amp draw: 8 amps
- Lighting outputs: 2
- Approvals: Exceeds acoustical and environmental requirements, SAE J1849, California Title 13

PART	DESCRIPTION
SS650-013	Four mode economy siren
SS651-013	Four mode economy siren separate switch panel

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FOR MORE INFORMATION VISIT OUR WEBSITE. STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC 455 Rochester St., Avon, NY 14414 Phone: 585-226-9500 | Fax: 888-478-2797



SF061 Rev-C 05-11-2023