

257HETL SERIES



Specs & Features:

- Halo ECE REG 65 LED light
- 122.4 Double flashes per minute (2.04CPS)
- Rugged die-cast metal, universal flange base:
- 3-hole permanent mount
- 25mm pipe mount
- optional magnet/vacuum magnetic mount with cigarette plug adapter
- durable polycarbonate, twist on/off lens
- Extremely low current draw
- Completely encapsulated circuit for increased weather and shock resistance
- Dimensions: (short dome) 120mm tall x 162mm dia.
4-3/4" tall x 6-13/32" dia.
(tall dome) 170mm tall x 162mm dia.
6-11/16" tall x 6-13/32" dia.
- Voltage: 9-32V DC
- Amps: 0.6 amps @ 12V DC, 0.3 amps @ 24V DC

* Meets ECE REG 10 and REG 65 specifications

Model Numbers / Descriptions:

- 257HETCL: 12 LED, 3 bolt fixing, tall lens
257HETSL: 12 LED, 3 bolt fixing, short lens
257HETCLM: 12 LED, magnet mount, tall lens
257HETSLM: 12 LED, magnet mount, short lens
257HETCLV: 12 LED, vacuum magnet mount, tall lens
257HETSLV: 12 LED, vacuum magnet mount, short lens

