

ULB9 & ULB9-1 \*



**ULB9S & ULB9S-1 \*** 



**ULB9E & ULB9E-1 \*** 




ULB9LDC & ULB9LDC-1 \*

SEE ELECTRICAL SPECS ON PAGE 2

**ULB9 HOUSING DIMENSIONS** 





UNLESS OTHERWISE SPECIFIED DRAWN BY:




	( X = INCLUDED WITH LIGHT				
SERIES	274-ULB9BKT	P30019-253	SULB9-HOOD-1		
ULB9 & ULB9-1	X	0	0		
ULB9S & ULB9S-1	0	-	Х		
ULB9E & ULB9E-1	0	-	X		
ULB9LDC & ULB9LDC-1	0	=	Х		
VOLTAGE	10-16 vdc ALL MODELS				
TEMPERATURE RANGE ALL MODELS: -30C TO +50C					

\* MODELS ENDING "-1" HAVE 12' CABLE, OTHERS ARE 12' LONG CIG PLUG





STAR HEADLIGHT & LANTERN CO., INC.



DIMENSIONS ARE IN INCHES	DRAWING APPROVED BY ECR	-				
TOLERANCES:	STAR HEADLIGHT & LANTERN CO., INC.,					
ANGULAR: ± 2 DEG.		F11.(303) 226-9300 Fax. (303) 226-2029				
.X ± .100 .XX ± .020 .XX + .005		MODEL: ULB9, ULB9S, ULB9E, ULB9LDC				
.XXXX ± .001		TITLE:				
ROHS COMPLIANT: NO		ULE	39 SERIES MODEL DRAW	ING		
MATERIAL: NA			DWG. NO. REV ULB9 SERIES C			
FINISH:						
NA		SCALE: 1:8	DO NOT SCALE FROM DRAWING SHEET	T 1 OF 2		
	TOLERANCES: ANGULAR: ± 2 DEGX ± .100 .XX ± .020 .XXX ± .001 .XXX ± .001  RoHS COMPLIANT: NO  MATERIAL: NA	TOLERANCES:  ANGULAR: ± 2 DEG.  .X ± .100  .XX ± .020  .XXX ± .005  .XXX ± .001  ROHS COMPLIANT: NO  TITLE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAR HEADLIGHT & LANTERN CO., INC ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC. IS STRICTLY PROHIBITED.  MA  FINISH:	DIMENSIONS ARE IN INCHES  TOLERANCES: ANGULAR: ± 2 DEG. X ± 1.100 XX ± 1.020 XXX ± 0.020 XXX ± 0.005 XXX ± 0.001 XXX ± 0.005 XXXX ± 0.005 XXXXX ± 0.005 XXXXX ± 0.001 XXXX ± 0.001 XXX ± 0.001 XX ± 0.001 XXX ± 0.001 XX ± 0.001 X	TOLERANCES:  ANGULAR: ± 2 DEG.  X ± 1.00  XX ± 0.005  XXX ± 0.01  XXX ± 0.01		

	AMP DRAW		
MODEL SERIES	AVERAGE	PEAK	
ULB9 and ULB9-1			
-AA (AMBER / AMBER)	0.4	1.4	
-AB (AMBER / BLUE)	0.4	1.4	
-AG (AMBER /GREEN)	0.4	1.4	
-AR (AMBER / RED)	0.5	1.5	
-AW (AMBER / WHITE)	0.4	1.4	
-BB (BLUE / BLUE)	0.4	1.3	
-BW (BLUE / WHITE)	0.4	1.3	
-GG (GREEN / GREEN)	0.4	1.3	
-GW (GREEN / WHITE)	0.4	1.3	
-RB (RED / BLUE)	0.4	1.4	
-RR (RED / RED)	0.4	1.4	
-RW (RED / WHITE)	0.4	1.4	
-WW (WHITE / WHITE)	0.4	1.3	
ULB9S and ULB9S-1 ALL MODELS	0.5	1.6	
ULB9E and ULB9E-1			
-AA (AMBER / AMBER)	0.3	0.9	
-AW (AMBER / WHITE)	0.3	0.9	
-AB (AMBER / BLUE)	0.3	0.9	
-AG (AMBER/GREEN)	0.3	0.9	
-BB (BLUE/BLUE)	0.3	0.9	
-RB (RED / BLUE)	0.2	0.6	
-RW (RED / WHITE)	0.2	0.6	
-WW (WHITE/WHITE)	0.3	0.9	
ULB9LDC and ULB9LDC-1			
-AW (AMBER / WHITE)	0.6	0.9	
-BW (BLUE / WHITE)	0.6	0.9	
-RB (RED / BLUE)	0.5	0.9	
-RW (RED / WHITE)	0.5	0.9	
-RBWW (RED/BLUE/WHITE/WHITE)	0.5	0.9	
-AAWW (AMBER/AMBER/WHITE/WHITE)	0.7	0.9	
-RRBB (RED/RED/BLUE/BLUE)	0.6	0.9	
-BBWW (BLUE/BLUE/WHITE/WHITE)	0.7	0.9	
-RRWW (RED/RED/WHITE/WHITE)	0.6	0.9	

REV.	ECR	DESCRIPTION	DATE
-	12513	INITIAL DRAWING REQUEST	3/19/15
Α	4/22/15		
В	12848	ADDED AMBER/BLUE AND AMBER/GREEN FOR ULB9E SERIES	6/26/2015
C	13029	ADDED NEW ULB9LDC MODELS, -RBWW, -AAWW, -RRBB, -BBWW AND -RRWW	9/17/2015

MODEL *	COLOR	FUNCTION	WIRE GAGE
ULB9-1, ULB9S-1 & ULB9E-1			
	BLACK	NEG (-) GROUND	20AWG
	RED	POS (+) 12VDC POWER	20AWG
	GREEN	PATTERN SELECT	20AWG
	WHITE	SYNC	20AWG
ULB9LDC-1			
	BLACK	NEG (-) GROUND	20AWG
	RED	POS (+) 12VDC POWER for COLOR 1	20AWG
	GREEN	POS (+) 12VDC POWER for COLOR 2	20AWG
	WHITE	SNYC	20AWG

UNLESS OTHERWISE SPECIFIED	DRAWN BY:	SWN	STAR H	<b>EADLIGHT &amp; LANTE</b>	RN CO	INC
DIMENSIONS ARE IN INCHES	DRAWING AP	PROVED BY ECR	455 Rochester St. Avon NY 14414			
TOLERANCES: THE INFORMATION CONTAINED IN THIS ANGULAR: ± 2 DEG. DRAWING IS THE SOLE PROPERTY OF			Ph:(585) 226-9500 Fax: (585) 226-2029			
.XXXX ± .001	WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC.	TITLE:				
ROHS COMPLIANT: NO	IS STRICTLY PROF	HIBITED.	ULB9 SERIES MODEL DRAWING			1G
MATERIAL:			DWG. NO.			REV
FINISH:		ULB9 SERIES C				
NA			SCALE: 1:8	DO NOT SCALE FROM DRAWING	SHEET	2 OF 2