


REV.	ECR	DESCRIPTION	DATE
-	14598	INITIAL DRAWING REQUEST	08/22/17




SPECIFICATIONS:

TYPICAL INPUT VOLTAGE RANGE: 9-32VDC
TYPICAL CURRENT DRAW: 12.8VDC=0.45A
TYPICAL CURRENT DRAW: 25.6VDC=0.23A
TYPICAL LIGHT OUTPUT (8 WARM WHITE LED'S): 1144 lm PEAK
TYPICAL LIGHT OUTPUT (8 COOL WHITE LED'S): 1223 lm PEAK
TYPICAL LIGHT OUTPUT (8 PC AMBER LED'S): 880 lm PEAK
LUMEN MAINTENANCE: 85% LUMEN AFTER 100,000 HOURS OPERATION
OPERATING TEMPERATURE RANGE: -40C TO 55C
CONNECTIONS / FUNCTION:


- 18 AWG RED WIRE 18" LONG (POWER +)
- 18 AWG BLACK WIRE 18" LONG (GROUND -)
- 18 AWG GREEN WIRE 18" LONG (PATTERN SELECT -)
- 20 AWG WHITE WIRE 18" LONG (SYNCHRONIZATION)

1" NPT PIPE MOUNT

MATERIALS: OUTER DOME: VIRGIN POLYCARBONATE
BASE: POLYCARBONATE



266TCLFL-*



266TSLFL-*

MODELS	DESCRIPTIONS	CLASSIFICATIONS
266TCLFL-A	X-FIRE BEACON; AMBER; 9-32VDC; 1" PIPE MOUNT; 8 WARM WHITE LED'S; 4 WIRES; AMBER 6 INCH DOME	SAE: W3-1 17
266TCLFL-AC	X-FIRE BEACON; AMBER; 9-32VDC; 1" PIPE MOUNT; 8 PC AMBER LED'S; 4 WIRES; CLEAR 6 INCH DOME	TBD
266TCLFL-B	X-FIRE BEACON; BLUE; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRES; BLUE 6 INCH DOME	TBD
266TCLFL-C	X-FIRE BEACON; COOL WHITE; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRES; CLEAR 6 INCH DOME	TBD
266TCLFL-G	X-FIRE BEACON; GREEN; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRE; GREEN 6 INCH DOME	N/A
266TCLFL-R	X-FIRE BEACON; RED; 9-32VDC; 1" PIPE MOUNT; 8 WARM WHITE LED'S; 4 WIRE; RED 6 INCH DOME	TBD
266TSLFL-A	X-FIRE BEACON; AMBER; 9-32VDC; 1" PIPE MOUNT; 8 WARM WHITE LED'S; 4 WIRE; AMBER 4 INCH DOME	SAE: W3-1 17
266TSLFL-AC	X-FIRE BEACON; AMBER; 9-32VDC; 1" PIPE MOUNT; 8 PC AMBER LED'S; 4 WIRE; CLEAR 4 INCH DOME	TBD
266TSLFL-B	X-FIRE BEACON; BLUE; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRE; BLUE 4 INCH DOME	TBD
266TSLFL-C	X-FIRE BEACON; COOL WHITE; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRE; CLEAR 4 INCH DOME	TBD
266TSLFL-G	X-FIRE BEACON; GREEN; 9-32VDC; 1" PIPE MOUNT; 8 COOL WHITE LED'S; 4 WIRE; GREEN 4 INCH DOME	N/A
266TSLFL-R	X-FIRE BEACON; RED; 10-30VDC; 1" PIPE MOUNT; 8 WARM WHITE LED'S; 4 WIRE; RED 4 INCH DOME	TBD

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES

TOLERANCES:

ANGULAR: ± 2 DEG.	
.X	± .100
.XX	± .020
.XXX	± .005
.XXXX	± .001

RoHS COMPLIANT: Yes

MATERIAL:

N/A

FINISH:

N/A

DRAWN BY: MD

DRAWING APPROVED BY ECR

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAR HEADLIGHT & LANTERN CO., INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC. IS STRICTLY PROHIBITED.

STAR HEADLIGHT & LANTERN CO., INC.

455 Rochester St. Avon NY 14414
Ph:(585) 226-9500 Fax: (585) 226-2029

MODEL: 266TCLFL-*, 266TSLFL-*

TITLE: MODEL DRAWING

DWG. NO.

266TLFL

REV

-

SCALE: 1:4

DO NOT SCALE FROM DRAWING

SHEET 1 OF 1